



FINAWAX-PE 3

DESCRIPTION : Oxidised Polyethylene wax

SPECIFICATIONS : Appearance : White powder/beads
Acid Value : 17 max
Melting Point : 107 ± 5°C

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

APPLICATIONS :
- Suitable in RPVC blown film processing to eliminate the problems of flow lines
- Recommended for injection mouldings - bottles etc.
- Suitable for clear applications only when used within limits

PROPERTIES :
- Highly external lubricant and mould release agent
- Reduces sticking problems
- Limited compatibility with PVC
- Haziness/exudation problems do not occur when used within limits

USE LEVEL : 0.05 - 0.15 phr

STABILIZATION : Suitable for use with all commercially available stabilizers

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & its associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.