



FINAWAX VL

CHEMICAL DESCRIPTION : Amide wax

TYPICAL SPECIFICATIONS :

Appearance	:	Yellow Powder
Acid Value (mg KOH / gm)	:	12.0 max
Melting Point °C	:	115 ± 5 °C

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

FINAWAX VL is a vegetable oil based amide wax, possessing high solubility in the co-solvents.

APPLICATIONS

- Slip as well as antiblocking properties to polar polymer matrix such as EVA, acrylic based ionomer films and PVC
- Printing inks (Gravure-flexo, off-set lithographic)
- Flow improver for alkyd resins
- Carbon paper inks & metal decorating inks
- Anticorrosion additive in lubricating oils
- Water repellent properties to cement
- Suitable choice where, good antiblocking properties and printability is required.

PROPERTIES

- Effective slip and antiblocking properties
- Superior printability to the surface (suitable for Corona untreated films)
- Good re-printability, scratch resistance & scuff resistance
- Improved tape test performance
- Increased water resistance to the printed surface

SUGGESTED USE LEVEL : 0.5 to 1.0 % (in inks)

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & its associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.