



FINAWAX S

DESCRIPTION : Saturated primary amide (Stearamide)

SPECIFICATIONS : Appearance : White Powder/Beads/Pellets
Acid Value : 1.0 max
Melting Point : 100 ± 5°C

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

PROPERTIES : FINAWAX S is a refined vegetable based stearamide

APPLICATIONS :
- Finawax S is an antiblocking additive for polyolefin films.
- Helps to achieve high quality films at lower dosage of inorganic antiblocks when used in combination.
- Works as a lubricant in PVC, PS, synthetic rubbers and other resins
- Can be used in the flexographic, lithographic & carbon paper inks
- FINAWAX S is used as a cell stabilizer in PE foam production

METHOD OF USE :
- Masterbatch route
- During compounding step

USE LEVEL : 0.5 - 1.0 % on total compound weight

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & its associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.