



FINAFLEX 1100

DESCRIPTION : Viscosity depressant for PVC paste processing

SPECIFICATIONS : Appearance : Liquid (at 30 deg C)

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

APPLICATIONS : PVC plastisol and pastes

PROPERTIES :

- Effective viscosity reducer and regulator
- Can offer excellent homogenization of filler/pigment in PVC plastisols and pastes via improved dispersion
- Enables uniform consistency; thereby, superior coating quality
- Reduces pin-holes and thus, can offer overall better surface properties

METHOD OF USE : During compounding step

USE LEVEL : 5 to 10% of total plasticizer weight in the paste (as per end-use requirements)

STORAGE : It is recommended to store this product at room temperature. At lower temperature, it may crystallize due to its inherent characteristics. The crystallization is reversible when heated and has no influence on application properties.

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & its associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.