



FINALUX G 161

DESCRIPTION : Lubricant

SPECIFICATIONS : Appearance : Liquid (at 30 deg C)

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

APPLICATIONS :

- Processing rigid PVC and plasticized PVC
- Suitable for calendaring & blown film processes
- Highly recommended in clear rigid & soft calendared PVC films/sheets due to excellent solubility in PVC (can be used up to 2 phr)
- FINALUX G 161 can support stabilizers containing sulphur

PROPERTIES :

- Internal lubricant with release properties
- Good compatibility
- Suitable for use in transparent products
- Improved free flowing properties and non-stickiness
- Non-application: With lead stabilizers in brightly pigmented rigid PVC

METHOD OF USE & USE LEVEL :

- 0.5 to 1.5 phr for rigid PVC
- 0.5 to 1.0 phr for plasticized PVC

STORAGE : It is recommended to store this product at room temperature. At lower temperature, it may crystallize due to its inherent characteristics. The crystallization is reversible when heated and has no influence on application properties.

Disclaimer: Information given herein is in good faith but without guarantee since the conditions of use of the product are not in our control. Fine Organic Industries Ltd & it's associate companies expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes by the user and does not assume any liability or risk involved in the use of its products. We recommend that the actual user make tests to determine the suitability of a product for their particular application prior to use. User should refer to SDS and other relevant data for safe handling. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.